

Novaflex®

Static Conductor Hose

Static Conductor*

Medium Duty Material Handling Hose

A flexible conductive hose designed to allow for safe grounding during wet and dry material transfer operations. This hose is lightweight with a smooth interior for optimum flow.

Applications

Agricultural clean up, grain, seeds etc.
Wood chipping/ leaf collection
Pellet and powder transfer
Coal dust evacuation

Construction

Product code: 9NFSCAP
Material: TPR copolymer with rigid plastic external scuff guard
Diameters: 2" to 6"
Bend radius: 4" I.D. = 4.25"
Weight per/ft: 4"=1.4 lbs
Lengths: 2" to 4" 100 ft, 6" - 50 ft
Temperature Range: -40°F (-40°C) to +200°F (+93°C)
Colour: Red with Black scuff guard

*Conductivity of hose should be tested regularly. Test with OHMS meter using conductive fittings inserted into each end of hose.



Specification Chart

Size	O.D.	Working Pressure PSI	Vacuum Rating Inch/Hg	Bend Radius Inch	Standard Length	Approx Weight Lb/ft
2"	2.45"	40	29	2.25	100ft	.70
3"	3.6"	35	29	2.75	100ft	1.0
4"	4.8"	30	29	4.25	100ft	1.4
6"	6.925"	30	28	9.00	60ft	2.3

Temperature range: -20°F to +165°F

Standard color: Red with black external wearstrip

*Conductivity of hose should be tested regularly. Test with OHMS meter using conductive fittings inserted into each end of hose.

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

10.2020

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk