

Getting the most from a single source

Utility Food Grade

Novaflex®

Novaflex 1200/1201

Durable medium weight utility food grade fabric duct. This product possesses good abrasion resistance and fire retardant qualities.

Applications

Clean room environment Cool or hot air supply Air handling, fume control Meets FDA regulations Hospitals, food establishments, computer rooms UL94V-0 rated material Meets Federal Test Standard 191-A Method 5903

Construction

Product code: 3UL1200 Material: White acrylic on polyester Construction: mechanical bond, galvanized helix Diameters: 3" to 24" I.D. Larger sizes available Bend radius: 1.5 x I.D. Weight: 6" I.D. = 1.25 lbs/ft Length: 25 ft. Compression: 5:1 Temperature Range: -20°F (-29°C) to +250°F (121°C). *See also extruded SF-PVC and SF-TPU duct for food grade options Colour: White U-Lok 1201 - Available with stainless steel helix



Specification Chart

| I.D. | 3 | 4 | 5 | 6 | 8 | 10 | 12 |
|-------------------------|-----|-----|-----|-----|-----|-----|-----|
| Working Pressure/PSI | 3.6 | 3.2 | 2.7 | 2.6 | 1.8 | 1.4 | 1.2 |
| Negative Pressure. H.g. | 2 | 1.8 | 1.3 | 1.2 | 1.1 | .73 | .6 |
| Weight per Foot | .6 | .7 | .9 | 1.1 | 1.5 | 1.8 | 2.2 |

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: <u>www.novaflex.com</u> | <u>www.flexmaster.com</u>.

IN USA

North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270



New Jersey 1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

Indianapolis 7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

Email: sales@novaflex.com Website: www.novaflex.com

IN CANADA

Ajax, Ontario 555 Beck Crescent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145 www.novaflex.co.uk Email: sales@novaflex.co.uk