

Novaflex®

Extra Flexible Hose

Novaflex 6514 Extra Flexible

Connoisseurs Food & Beverage Hose Suction & Discharge

The connoisseur line of food hose is designed to meet the food processing industries demanding applications. Connoisseur is built in a variety of hose constructions utilizing a white chlorobutyl tube for non-oily applications that will not impart taste or odor. Meets FDA, USDA, and 3-A Sanitary Standards Authorized (#1376). Resistant to CIP solutions. This ultra smooth microbe resistant tube is built of special stainless steel mandrels for cleanliness.

Specifications

Tube: White chlorobutyl (full vacuum non oily applications Reinforcement: Multiple plies of polyester tire cord with helix wire

(microbe resistant)

Cover: Grey EPDM Corrugated

Length: 100 ft.

Temperature Range -40°F (-40°C) to +240°F (+116°C)

Cleaning in Place to 248°F (+120°C) Not for continuous steam service

Corrugated available with UHMWP cover



Part No.	I.D.	O.D.	Plies	WP psi	MBR	WT LBS/FT
6514WB-01000-00	1	1.50	2	150	3″	0.57
6514WB-01500-00	11/2	2.04	2	150	2"	0.92
6514WB-02000-00	2	2.66	2	150	3″	1.44
6514WB-02500-00	21/2	3.231	2	150	4"	1.97
6514WB-03000-00	3	3.82	2	150	5"	2.97
6514WB-04000-00	4	4.82	2	150	7″	3.84

Nova-Glide cover

14044 Olide Covel									
Part No.	I.D.	O.D.	Plies	WP psi	MBR	WT LBS/FT			
6514WBU-01000-00	1	1.50	2	150	3″	0.72			
6514WBU-01500-00	1½	2.06	2	150	2.5"	.94			
6514WBU-02000-00	2	2.57	2	150	3.5"	1.47			
6514WBU-02500-00	21/2	3.12	2	150	5.5"	2.03			
6514WBU-03000-00	3	3.71	2	150	6.5"	3.03			
6514WBU-04000-00	4	4.79	2	150	8.5"	3.91			

Nova-Glide is an UHMWP cover applied over the rubber cover to provide easy cleaning, low coefficient of friction and added abrasion.

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete

Terms and Conditions of Sale located on our web sites at: www.novaflex.com | www.flexmaster.com.

O5. 2021

IN USA

North Carolina

449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270 **New Jersey**

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215 Indianapolis

7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288 IN CANADA

Ajax, Ontario 555 Beck Cresent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk



Email: sales@novaflex.com Website: www.novaflex.com