

Novaflex®

Novalite Tank Truck Hose

Novaflex 3477

Novalite Tank Truck Hose

Recommended for the transfer of petroleum products with an aromatic content of up to 55%. Novalite has a unique design utilizing a flat corrugation design permitting extreme ease when flexing. Novalite is also excellent for the transfer of other oily products, such as fats, greases, vegetable oil, hydraulic fluid and a wide range of chemicals. This hose takes a very little force to flex the hose, compared to other constructions.

Fuel compatibility: Ethanol up to E85. Biodiesel up to B20

When coupling chemical and higher risk hoses, Novaflex® recommends the use of crimp couplings using interlocking crimp ferrules.

Specifications

Reinforcement: Multiple plies of Polyester tire cord with dual helix

wire

Cover: Black Oil & Abrasion Resistant Rubber

Length: 100ft (maximum)

Temperature range -40° (-40°C) to $+180^{\circ}$ F (+82°C)



Specification Chart

Product No	ID"	OD"	Plies	WP psi	MBR	Wt LBS/Ft
3477BT-01000-00	1	1.55"	2	150	2"	.6
3477BT-01250-00	11/4	1.80"	2	150	3"	.7
3477BT-01500-00	1½	2.15"	2	150	3"	5.9
3477BT-02000-00	2	2.68"	2	150	4"	1.2
3477BT-02500-00	21/2	3.20"	2	150	5"	1.45
3477BT-03000-00	3	3.73"	2	150	6"	1.9
3477BT-04000-00	4	4.73"	2	150	9″	2.6
3477BT 06000 00	6	6 75"	4	150	20"	5 31

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.re-flex.com | www.flex.master.com.

IN USA

North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

New Jersey

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

Indianapolis

7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

IN CANADA

Ajax, Ontario 555 Beck Crescent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk



Email: sales@novaflex.com Website: www.novaflex.com