

# **Novaflex®**

# **Petroleum Tank Truck Hose**

### Novaflex 3550

#### **Heavier Duty Petroleum Discharge Hose**

Designed to be flexible with a hose cover that provides extra abrasion resistance to meet the demanding requirements of industry. Handles all grades of petroleum with aromatic contents to 55%.

### **Specifications**

Tube: Black Nitrile

Reinforcement: Multiple plies tire cord with static wire

Cover: Black oil and abrasion resistant rubber

Length: 100 ft.

Temperature Range:  $-30^{\circ}F$  ( $-35^{\circ}C$ ) to  $+180^{\circ}F$  ( $+82^{\circ}C$ )

**Fuel Compatibility:** Ethanol up to E85. Biodiesel up to B20.

When coupling chemical and higher risk hoses, Novaflex® recommends the use of crimp couplings using interlocking crimp ferrules.



## **Specification Chart**

Part No.	I.D.	0.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3550BT-01000-00	1	1.52	2	n/a	n/a	250	0.57
3550BT-01500-00	1½	2.14	2	n/a	n/a	250	0.96
3550BT-02000-00	2	2.64	2	n/a	n/a	250	1.23
3550BT-02500-00	21/2	3.14	2	n/a	n/a	250	1.49
3550BT-03000-00	3	3.54	2	n/a	n/a	250	2.10
3550BT-04000-00	4	4.65	4	n/a	n/a	250	2.42
3550BT-06000-00	6	6.70	4	n/a	n/a	250	4.90

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: <a href="https://www.novaflex.com">www.novaflex.com</a> | <a href="https://www.flexmaster.com">www.flex.com</a> | <a href="https://www.flexmaster.com">www.flex.com</a> | <a href="https://www.flexmaster.com">www.flex.com</a> | <a href="https://www.flexmaster.com">www.flex.com</a> | <a href="https://www.flexmaster.com">www.flexmaster.com</a> | <a href="https://www.flexmaster.com">www.flex.com</a> | <a href="https://www.flexmaster.com">www.flexmaster.com</a> | <a href="https://www.flexmaster.com">www.flex.com</a> | <a href="https://www.flexmaster.com">www.flexmaster.com</a> |

#### **IN USA**

#### North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

# New Jersey

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

#### Indianapolis

7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

#### **IN CANADA**

Ajax, Ontario 555 Beck Crescent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

#### IN U.K.

### Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk

Email: sales@novaflex.com

