

# **Novaflex®**

## **Vapor Recovery Service**

**Uni-VR™ Hose\*** is ideal for use in petroleum and petrochemical vapor recovery systems in ship to shore, bottom loading and tank truck applications. This hose is lightweight and flexible. Manufactured to meet specification CFR33-154. Rated for full vacuum.

\*Available with a nylon or teflon tube and a polypropylene coated and stainless steel inner helix.

Available diameters: 1" to 10"

Maximum Length: 100 feet. (10"= 80 ft.)

Operating Temperature: -40°F to +212°F / -40°C to +100°C

Available with a yellow or orange cover.



Uni-CHEM® Composite Hose are manufactured in compliance with BS 5842 and are available with EN 13765 compliant construction. Marine Service Applications: All Uni-CHEM® hose styles are constructed to marine service specifications in accordance with US Coast Guard spec.154.500 and I.M.O regulations.

## **Specification Chart**

ID (INS)	1	1.5	2	3	4	6	8	10
ID (OUT)	1.5	1.9	2.4	3.4	4.4	6.75	9.0	11.5
Max WP PSI	100	100	100	100	100	100	100	100
Burst Pres PSI	200	200	200	200	200	200	200	200
Bend Rad. Inches	4.0	5.0	6.0	7.9	11.9	22.0	30.0	40.0
Weight LB/FT	.58	.79	1.18	1.88	2.70	7.0	10.0	13.0

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: <a href="https://www.novaflex.com">www.novaflex.com</a> | <a href="https://www.novaflex.com">www.z-flex.com</a> | <a href="https://www.novaflex.com">www.z-flex.com</a> | <a href="https://www.novaflex.com">www.z-flex.com</a> | <a href="https://www.novaflex.com">www.z-flex.com</a> | <a href="https://www.novaflex.com">www.flex.master.com</a>.

10.2023

#### **IN USA**

North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

#### **New Jersey**

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

#### Indianapolis

7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

#### IN CANADA

Ajax, Ontario 555 Beck Cresent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

#### IN U.K.

### Bromborough, Wirral

18 Plantation Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk



Email: sales@novaflex.com Website: www.novaflex.com