

Water Hose - Fire Engine Suction

Novaflex 2160 Water Removal and Hydrant Services



Premium quality heavy duty hose designed for suction and discharge applications commonly found in water removal and hydrant service on fire trucks

Construction:

Tube: SBR

Reinforcement: Multiple plies of polyester tire cord with helix

Cover: Smooth SBR

Length: Available in specific lengths with cuff ends - price on application

Temperature Range: -40° to 180°F

Meets or exceeds NFPA #189 & 1901 requirements

Part No.	I.D.	O.D.	Plies	WP psi	Min Order Lgth	WT LBS/ FT
2160BS-02500-00	2	3.25	2	150	100'	2.46
2160BS-03000-00	2 1/2	3.687	2	150	100'	2.88
2160BS-04000-00	3	4.25	2	150	50'	3.77
2160BS-04500-00	4	4.687	4	150	50'	5.16
2160BS-05000-00	5	5.75	4	150	50'	5.77
2160BS-06000-00	6	6.75	4	150	50'	7.03

Novaflex 2161 Water Removal and Hydrant Services



Premium quality heavy duty hose designed for suction and discharge applications commonly found in water removal and hydrant service on fire trucks.

Construction:

Tube: SBR

Reinforcement: Multiple plies of polyester tire cord with helix

Cover: Corrugated black EPDM cover

Length: up to 100 ft

Temperature Range: -40° to 180°F

Hose comes with 6" cuffed ends. Meets or exceeds NFPA #189 & 1901 requirements.

Part No.	I.D.	O.D.	Plies	WP psi	Min Qty	WT LBS/ FT
2161BS-02500-00	2	3.04	2	150	4	2.42
2161BS-03000-00	2 1/2	3.54	2	150	4	2.9
2161BS-04000-00	3	4.54	2	150	2	3.47
2161BS-04500-00	4	4.687	4	159	2	5.2
2161BS-05000-00	5	5.54	4	150	2	5.88
2161BS-06000-00	6	6.58	4	150	2	7.36