



# NOVAFLEX® Flame Retardant Thermoplastic Duct

Designed for use in volatile environments.

Dust control.

High temperature exhaust, including sparks.

THE  
**NOVAFLEX**  
GROUP   
[www.novaflex.com](http://www.novaflex.com)

# Novaflex® Flame Retardant Thermoplastic Rubber

## Flexible Fume Control Duct in Flame Retardant Thermoplastic Rubber

This flame retardant welding fume extraction duct and cable cover is designed specifically for welding environments including sparks and slag. Flexibility allows fit around tight corners and limited spaces. Ideal for dust and fume removal. Manufactured of UL 94V0 approved material and RoHS compliant material.

### Applications

Welding fume exhaust  
High temperature fume control  
Smoke and dust control for manufacturing processes  
Ideal for use as flame retardant protective jacket for cables, beverage lines etc.

### Product Specifications

Product code: 9SFTPRV\_FR  
Material: Flame retardant thermoplastic rubber  
Standard diameters: 2" to 12"  
Weight: 6" = .77 lbs  
Standard lengths: 25 ft & 50 ft to 8" diameter, 25 ft - 10" diameter and up.  
Compression ratio: 2:1  
Temperature range: -40°F (-40°C) to +275°F (+135°C), continuous, 300°F (+149°C) intermittent  
Standard color: black with orange wear strip.  
\*available with and without encapsulated wire



## Specification Chart

Size ID (in)	Min in. for 90° Bend	Bend Radius	Friction Loss Straight Run 100' (in Wg)	Friction Loss 90° 100' (in Wg)	Positive W. P. (PSIG)	Neg. W.P. (vacuum rating in Hg)	Wgt (per foot)	Crush Tests ½ ID (lbs per foot)
2"	8.0"	3.0"	1.68	1.8	8.5	26	0.33	790
3"	9.0"	3.5"	1.6	1.72	7.5	24	0.39	690
4"	11.5"	4.5"	1.3	1.43	7.3	20	0.49	500
5"	13.5"	5.5"	1.23	1.34	7.2	16	0.66	400
6"	14.5"	6.5"	1.2	1.32	7	12	0.77	375
8"	19.0"	8.5"	0.7	0.77	6.7	5	1	320
10"	21.0"	10.0"	0.68	0.75	5.5	4.5	1.12	290
12"	24.5"	11.5"	0.65	0.72	4.7	4	1.23	250

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: [www.novaflex.com](http://www.novaflex.com) | [www.z-flex.com](http://www.z-flex.com) | [www.flexmaster.com](http://www.flexmaster.com).

05.2026

### IN USA

#### North Carolina

449 Trollingwood Road  
Haw River, NC 27258  
tel (336)578-2161  
fax (336)578-5554  
800-334-4270

#### New Jersey

1024 Industrial Drive  
West Berlin, NJ 08091  
tel (856)768-2275  
fax (856)768-2385  
800-225-0215

#### Indianapolis

7812 Moller Road  
Indianapolis, IND 46268  
tel (317)334-1444  
fax (317)334-1535  
800-526-6288

### IN CANADA

#### Ajax, Ontario

555 Beck Crescent  
Ajax, ON L1Z 1C9  
tel (905)686-5200  
fax (905) 686-8349  
800-563-3539

### IN U.K.

#### Bromborough, Wirral

18 Plantation Park 2, Power Road  
Bromborough, Wirral UK CH62 3QT  
tel 44(0)151-334-0873  
fax 44(0)151-334-7145  
[www.novaflex.co.uk](http://www.novaflex.co.uk) Email: [sales@novaflex.co.uk](mailto:sales@novaflex.co.uk)