

Novaflex®

Nitrile Suction & Discharge Hose

Novaflex 6300

Nitrile Food 150 Suction & Discharge Hose

Recommended for the food transfer application that demands both flexibility and ruggedness with a clean white FDA grade tube. Meets FDA, USDA & 3A sanitary standards Authorized #1376. The food grade nitrile tube is odorless and tasteless for those oily transfer applications. Excellent for suction and discharge applications. This ultra smooth microbe resistant tube is built on special stainless steel mandrels for cleanliness.

Construction:

Tube: FDA white nitrile

Reinforcement: Multiple plies of polyester tire cord with helix wire

Cover: Blue PVC nitrile. Length: 100ft.

Temperature Range: -40°F (-40°C) to +210°F (+99°C)

(Cleaning In Place to 248°F (+120°C) Not for continuous steam service



Meets or exceeds the requirement of the Canadian Food Inspection Agency (File:N267)

Non-stock orders - (other color hose covers red, black, white) are available and require a 400ft minimum order per I.D.

Specification Chart

Product No	ID" in	ID mm	OD" in	OD" mm	VAC Bar	PSI	WP Bar	MBR in	MBR mm	Kg/m
6300WF00750-00	.75	19.05	1.25	31.8	.9	150	10.34	4	101.6	0.60
6300WF01000-00	1	25.4	1.5	38.1	.9	150	10.34	5	127.0	0.74
6300WF01500-00	1.5	38.1	2.0	50.8	.9	150	10.34	6	152.4	1.06
6300WF02000-00	2	50.8	2.55	63.5	.9	150	10.34	7	177.8	1.41
6300WF02500-00	2.5	63	2.94	74.7	.9	150	10.34	8	200	1.73
6300WF03000-00	3	76.2	3.52	89.4	.9	150	10.34	9	228.6	2.25
6300WF04000-00	4	101.6	4.52	114.8	.9	150	10.34	12	304.8	2.95

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

07.2020

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905)686-8349
800-563-3539

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IN 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288