

Novaflex®

Dock Hose

Novaflex 3277 Smooth Cover Dock Hose

Meets BS EN 1765, Type S15.

A special design to meet international requirements, complies with the BS EN 1765 standard for Type S 15 dock hose. This hose has built in nipples with flanges but is available with crimped on coupling & flanges through 8" ID. All hoses come with test certificates. Tube resistant to 55% aromatic fuels.

Specifications

Tube: NBR

Reinforcement: Polyester tire cord plies with helix wire

Cover: Black NBR blend

Ends: Straight (built in nipples & crimped available)

Length: 100 ft

Temperature Range: 30°F (-35°C) to +200°F (+93°C)



When coupling chemical and higher risk hoses, Novaflex® recommends the use of crimp couplings using interlocking crimp ferrules.

Fuel Compatibility:
Ethanol up to E85
Biodiesel up to B20

Specification Chart

Part No	ID		OD		MBR		VAC	WP	Weight		
	in	mm	in	mm	in	mm	(Hg)	PSI	Bar	Lbs/ft	Kg/m
3277BT-06000-00	6	150	7.35	187	36	915	Full	220	15	8.3	27.2
3277BT-08000-00	8	200	9.45	240	48	1220	Full	220	15	12.69	41.6
3277BT-10000-00	10	254	11.92	303	60	1525	Full	220	15	20.35	66.7
3277BT-12000-00	12	300	13.98	355	72	1829	Full	220	15	23.95	78.5

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

11.2020

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IN 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288