

Novaflex®

Petroleum Transfer Hose

Oilfield Frac Hose

Novaflex 3274BT (3274BTU)

Oil Field Fracturing Hose is designed for higher pressure suction and discharge applications that require working pressures up to 400 psi. This hose has a rugged design and has an all weather cover which is resistant to oil, cuts, abrasion and gouges. This hose can have a UHMWPP wear cover added for additional abrasion resistance (U version). The tube is resistant to petroleum products with aromatic content to 55%.

Specifications

Tube: Nitrile

Reinforcement: Multiple plies polyester tire cord and helical wire.

Cover: a. Smooth black oil, ozone & UV resistant compound.
b. Optional UHMWPP wear cover in the U version

Temperature range: -40°F (-40°C) to +200°F (+93°C)

Marking: Novaflex 3274BT (3274BTU) Oil Field

Frac/Petroleum Discharge

Fuel Compatibility: Ethanol up to E85. Biodiesel up to B20

When coupling chemical and higher risk hoses, Novaflex® recommends the use of crimp couplings using interlocking crimp ferrules



Specification Chart

| Product No | ID" | OD" | WP | MBR | Wt/Ft |
|-----------------|-----|------|---------|-----|----------|
| 3274BT-04000-00 | 4 | 4.82 | 400 psi | 40" | 4.12 lbs |
| 3274BT-04000-00 | 4 | 5.09 | 500 psi | 48" | 5.91 lbs |

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

12.2018

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk