

# Novaflex®

# Industrial Vacuum Hose

## Novaflex 5020 Industrial Vacuum Hose

Designed for light duty commercial vacuum cleaners used in foundries, factories and similar applications where a flexible and lightweight construction is preferred.

### Specifications

Tube: 1/16" abrasion resistant

Reinforcement: Fabric with helix wire

Cover: Black corrugated

Length 50 ft.

Ends: Plain (Also available with cuffs)

Temperature range: Range: -40°F (-40°C) to +160°F (+71°C)  
(Depending on compound).

Also available in static-dissipating tube, 5020BG-XXXX-04

Novaflex5020YG - Yellow Novaware tube  
superior abrasion resistance



## Specification Chart

| Part No.      | I.D. | O.D. | Plies | MBR (in) | WT LBS/FT |
|---------------|------|------|-------|----------|-----------|
| 5020-01000-00 | 1    | 1.38 | 1     | 3        | 0.4       |
| 5020-01250-00 | 1¼   | 1.63 | 1     | 4        | 0.4       |
| 5020-01500-00 | 1½   | 1.88 | 1     | 5        | 0.5       |
| 5020-02000-00 | 2    | 2.38 | 1     | 8        | 0.7       |
| 5020-02500-00 | 2½   | 2.88 | 1     | 8        | 0.8       |
| 5020-03000-00 | 3    | 3.38 | 1     | 9        | 0.9       |
| 5020-04000-00 | 4    | 4.38 | 1     | 12       | 1.9       |

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: [www.novaflex.com](http://www.novaflex.com) | [www.z-flex.com](http://www.z-flex.com) | [www.flexmaster.com](http://www.flexmaster.com).

04.2020

### IN USA

#### North Carolina

449 Trollingwood Road  
Haw River, NC 27258  
tel (336)578-2161  
fax (336)578-5554  
800-334-4270

#### New Jersey

1024 Industrial Drive  
West Berlin, NJ 08091  
tel (856)768-2275  
fax (856)768-2385  
800-225-0215

#### Indianapolis

7812 Moller Road  
Indianapolis, IND 46268  
tel (317)334-1444  
fax (317)334-1535  
800-526-6288

### IN CANADA

#### Ajax, Ontario

555 Beck Crescent  
Ajax, ON L1Z 1C9  
tel (905)686-5200  
fax (905) 686-8349  
800-563-3539

### IN U.K.

#### Bromborough, Wirral

18 Candy Park 2, Power Road  
Bromborough, Wirral UK CH62 3QT  
tel 44(0)151-334-0873  
fax 44(0)151-334-7145  
[www.novaflex.co.uk](http://www.novaflex.co.uk) Email: [sales@novaflex.co.uk](mailto:sales@novaflex.co.uk)