

# Novaflex®

# Vapor Recovery Service

**Uni-VR™ Hose\*** is ideal for use in petroleum and petrochemical vapor recovery systems in ship to shore, bottom loading and tank truck applications. This hose is lightweight and flexible. Manufactured to meet specification CFR33-154. Rated for full vacuum.

\*Available with a nylon or teflon tube and a polypropylene coated and stainless steel inner helix.

Available diameters: 1" to 10"  
 Maximum Length: 100 feet. (10"= 80 ft.)  
 Operating Temperature: -40°F to +212°F / -40°C to +100°C  
 Available with a yellow or orange cover.



Uni-CHEM® Composite Hose are manufactured in compliance with BS 5842 and are available with EN 13765 compliant construction. Marine Service Applications: All Uni-CHEM® hose styles are constructed to marine service specifications in accordance with US Coast Guard spec. 154.500 and I.M.O regulations.

## Specification Chart

ID	1	1.5	2	3	4	6	8	10
<b>OD</b>	<b>1.5</b>	<b>1.9</b>	<b>2.4</b>	<b>3.4</b>	<b>4.4</b>	<b>6.75</b>	<b>9.0</b>	<b>11.5</b>
<b>Max WP PSI</b>	100	100	100	100	100	100	100	100
<b>Burst Pres PSI</b>	400	400	400	400	400	400	400	400
<b>Bend Rad. Inches</b>	4.0	5.0	6.0	7.9	11.9	22.0	30.0	40.0
<b>Weight LB/FT</b>	.58	.79	1.18	1.88	2.70	7.0	10.0	13.0

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: [www.novaflex.com](http://www.novaflex.com) | [www.z-flex.com](http://www.z-flex.com) | [www.flexmaster.com](http://www.flexmaster.com).

12.2024

### IN USA

#### North Carolina

449 Trollingwood Road  
 Haw River, NC 27258  
 tel (336)578-2161  
 fax (336)578-5554  
 800-334-4270

#### New Jersey

1024 Industrial Drive  
 West Berlin, NJ 08091  
 tel (856)768-2275  
 fax (856)768-2385  
 800-225-0215

#### Indianapolis

7812 Moller Road  
 Indianapolis, IND 46268  
 tel (317)334-1444  
 fax (317)334-1535  
 800-526-6288

### IN CANADA

#### Ajax, Ontario

555 Beck Crescent  
 Ajax, ON L1Z 1C9  
 tel (905)686-5200  
 fax (905) 686-8349  
 800-563-3539

### IN U.K.

#### Bromborough, Wirral

18 Plantation Park 2, Power Road  
 Bromborough, Wirral UK CH62 3QT  
 tel 44(0)151-334-0873  
 fax 44(0)151-334-7145  
 www.novaflex.co.uk Email: sales@novaflex.co.uk