

Novaflex®

Vapor Recovery Service

Uni-VR™ Hose is ideal for use in petroleum and petrochemical vapor recovery systems in ship to shore, bottom loading and tank truck applications. This hose is lightweight and flexible. Manufactured to meet specification CFR33-154.

Uni-VR™*

G-High Tensile Galvanized Carbon Steel Inner Helix
G-High Tensile Galvanized Carbon Steel Outer Helix
Yellow Cover

*Available with a nylon or teflon tube and a polypropylene coated and stainless steel inner helix.

Available diameters: 1" to 10"

Maximum Length: 100 feet. (10" - 80ft)

Operating Temperature: -40°F to +212°F / -40°C to +100°C

Available with a yellow or orange cover.



Uni-CHEM® Composite Hose are manufactured in compliance with BS 5842 and are available with EN 13765 compliant construction. Marine Service Applications: All Uni-CHEM® hose styles are constructed to marine service specifications in accordance with US Coast Guard spec. 154.500 and I.M.O regulations.

Specification Chart

ID (INS)	1	1.5	2	3	4	6	8	10
ID (OUT)	1.5	1.9	2.4	3.4	4.4	6.75	9.0	11.5
Max WP PSI	100	100	100	100	100	100	100	100
Burst Pres PSI	400	400	400	400	400	400	400	400
Bend Rad. Inches	4.0	5.0	6.0	7.9	11.9	22.0	30.0	40.0
Weight LB/FT	.58	.79	1.18	1.88	2.70	7.0	10.0	13.0

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

10.2020

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk