

Novaflex®

Special Petroleum Service Hose

Uni-ZENE™

Uni-ZENE™ GG special service petroleum hose is designed to handle modern gasoline additives such as MTBE, ethanol and benzene.

Suitable for transferring petroleum and aromatic products in production, refinery and distribution facilities as well as all hose loading arms in bottom loading operations. Also recommended for all JP aviation fuels.

Constructed with an effective combination of polyamide, polyester and polypropylene film and fabric to meet the demands of today's additives. All hoses can be color coded to API color codes. Rated for full vacuum.

Available diameters: 1" to 10"

Maximum length: 100 ft. (10" = 50 ft.)

Operating Temperature: -40°F to +250°F / -40°C to +121°C



Uni-CHEM® Composite Hose are manufactured in compliance with BS 5842 and are available with EN 13765 compliant construction. Marine Service Applications: All Uni-CHEM® hose styles are constructed to marine service specifications in accordance with US Coast Guard spec. 154.500 and I.M.O regulations.

Specification Chart

ID (INS)	1	1.5	2	3	4	6	8	10
ID (OUT)	1.5	1.9	2.4	3.4	4.4	7.0	9.4	11.5
Max WP PSI	250	250	250	250	250	250	250	200
Burst Pres PSI	1000	1000	1000	1000	1000	1000	1000	800
Bend Rad. Inches	4.0	5.0	6.0	7.9	11.9	22.0	30.0	40.0
Weight LB/FT	.60	.80	1.60	2.40	3.20	7.2	11.0	14.5

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

10.2020

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk