



Single-wall - AL 29-4C® Stainless Steel

- 3" through 24" diameters.
 - Complete systems From starter to termination.
 - Cut-to-Length OR Adjustable Lengths available.
 - Up to 10-foot lengths available in 3" & 4" diameters.
- Gasket joint connections all diameters.
 - Double Fail-Safe™ self sealing gaskets.
 - Factory installed Air-tight & Water-tight seals.
 - No sealant required saves installation time and money.
 - 1¾" overlapping secure-joint 3" through 12" diameters.
 - 2¾" overlapping secure-joint 14" through 24" diameters.
- Gear Clamp closure system.
 - Field tested and time proven for more than 10 years.
 - Easy to install using standard tools.
 - On exterior of female joint.
 - Easy to replace if damaged during installation.
 - No screws No tabs to bend No joint bands or coupling to install.
- Fusion welded pipe seams.
 - High tech welding no filler material used.
 - Air & Water tight seams.
- Equipment starter adapters available.
 - For most popular Category II, III, & IV gas fired appliances.
 - Boilers Water Heaters Unit Heaters Tankless WH's.

Z-VENT[™] is manufactured by Z-Flex® US, a Novaflex Group Company

Canada: 452 Attwell Drive, Etobicoke, ON M9W 5C3 tel: 416.679.0045 ● fax: 416.679.0051 20 Commerce Park North, Bedford, New Hampshire tel: 603.669.5136 800.654.5600 ● fax: 603.669.0309 USA:





Double-wall - AL 29-4C® Stainless Steel

- 3" through 24" diameters.
 - 1" airspace insulated double-wall vent system.
 - AL 29-4C[®] Stainless Steel (SS) inner gas vent conduit.
 - 304 Stainless Steel (SS) outer jackets.
 - Complete systems From starter to termination.
 - 4-foot lengths available 3 8-inch diameters.
 - Elbows, Tee's, Supports, Flashings, etc.
 - Adjustable lengths all diameters.
- Gasket joint connection all diameters.
 - Double Fail-Safe[™] self sealing gaskets.
 - Air-tight & Water-tight joint seal.
 - Factory installed.
 - No sealant required saves installation time.
 - Insures proper seal every time.
- Snap-secure joining system.
 - Fast Simple –Secure.
 - NO tools required.
 - 1¾" overlapping secure-joint 3" through 12" diameters.
 - 2³/₄" overlapping secure-joint 14" through 24" diameters.
- Fusion welded pipe seams.
 - High tech welding no filler material used.
 - Insure system anti-corrosive properties.
 - Air & Water tight seams.

Z-VENT[™] is manufactured by Z-Flex® US, a Novaflex Group Company

Canada: 452 Attwell Drive, Etobicoke, ON M9W 5C3 tel: 416.679.0045 • fax: 416.679.0051 **USA:** 20 Commerce Park North, Bedford, New Hampshire tel: 603.669.5136 800.654.5600 • fax: 603.669.0309